

NEW PRODUCT  
NOW AVAILABLE



# VELLA

VENETIAN PLASTER SYSTEMS



## VELLA LISCIO ULTRA SHEEN PLASTER

*Vella Liscio Ultra Sheen Plaster is designed as a top coat over a Vella Venetian Plaster base coat, to achieve a high sheen polished plaster finish.*

### APPLICATION

**STEP 1:** Prepare by covering areas not to be plastered. Apply base coat to surface as evenly as possible. Cover textures or blemishes using a trowel, spatula or paint roller. Vella Liscio Ultra Sheen Plaster may be used over new or previously painted surfaces. Surfaces must be dry, clean, firm and free of dust, dirt, oil, wax, loose paint, wallpaper and plaster.

- ❖ When using a paint roller, use a trowel or spatula to smooth over any stipple left by the roller before the plaster dries. Plaster should dry overnight. Depending on weather conditions, fans may be used to speed up the drying process.

**STEP 2:** After Vella Base Coat dries, scrape any ridges or defects using a trowel or spatula, making base coat smooth to the touch. Remove any debris or dust away from corners and masked off areas before applying Vella Liscio Ultra Sheen Plaster. Using a random pattern apply a thin coat of Vella Liscio Ultra Sheen Plaster over the entire base coat using a trowel or spatula.

- ❖ Additional troweling of Vella Liscio Ultra Sheen Plaster after completing will produce an extremely high sheen to the finished surface.

**STEP 3:** After second coat dries (usually 4 hours, depending on weather conditions), apply a thin coat of Vella Premium Plaster Wax or sealer by sponge, rag or trowel to the entire surface. Final polishing of the surface should be done approximately 15 minutes after waxing using a dry rag or mechanical buffer.

### MIXING

Add desired color (store will mix). If adding your own color, mix with drill and paddle.

### COVERAGE

Vella Liscio Ultra Sheen Plaster covers approximately 450 square feet per gallon depending on application of product and surface preparation.

### STORAGE

Store at room temperature with container tightly sealed.

### CLEAN UP

Wash tools with water.

### CAUTION

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only.

If sanding is necessary, use a dust-particulate respirator approved by NIOSH/MSHA.



| VELLA PART# | DESCRIPTION                      | SIZE     | WEIGHT   | UPC CODE        |
|-------------|----------------------------------|----------|----------|-----------------|
| 30003       | VELLA LISCIO ULTRA SHEEN PLASTER | 3.5 GAL. | 39 LBS.  | 0 00516 30003 8 |
| 30002       | VELLA LISCIO ULTRA SHEEN PLASTER | 1 GAL.   | 11 LBS.  | 0 00516 30060 1 |
| 30006       | VELLA LISCIO ULTRA SHEEN PLASTER | 1 QT.    | 2.5 LBS. | 0 00516 30006 9 |

### SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM

**SUBMITTAL APPROVALS**

JOB NAME:

CONTRACTOR:

DATE:

SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • [WWW.VELLAPLASTER.COM](http://WWW.VELLAPLASTER.COM)

NEW PRODUCT  
NOW AVAILABLE



# VELLA

VENETIAN PLASTER SYSTEMS



## VELLA PREMIUM VENETIAN PLASTER

### APPLICATION

**STEP 1:** Prepare by covering areas not to be plastered. Apply base coat to surface as evenly as possible. Cover textures or blemishes using a trowel, spatula or paint roller. Vella Premium Venetian Plaster may be used over new or previously painted surfaces. Surfaces must be dry, clean, firm and free of dust, dirt, oil, wax, loose paint, wallpaper and plaster.

- ❖ When using a paint roller, use a trowel or spatula to smooth over any stipple left by the roller before the plaster dries. Plaster should dry overnight. Depending on weather conditions, fans may be used to speed up the drying process.

**STEP 2:** After plaster base coat dries, in a random pattern apply a thin coat of plaster over the base coat using a trowel or spatula.

*Tip: Any ridges in the base coat may be scraped off with a spatula prior to applying the second coat. Tools should be clean and smooth before applying plaster. Use fine sandpaper to keep tools smooth and free of nicks.*

- ❖ Additional troweling of plaster after the second coat has set up will produce a higher sheen to the finished surface.

**STEP 3:** After second coat dries (usually 4 hours, depending on weather conditions), apply a thin coat of Vella Premium Plaster Wax or sealer by sponge, rag or trowel to the entire surface. Final polishing of the surface should be done approximately 15 minutes after waxing using a dry rag or mechanical buffer.

### MIXING

Add desired color (store will mix). If adding your own color, mix with drill and paddle.

### COVERAGE

Vella Premium Venetian Plaster covers approximately 100 square feet per gallon depending on textures and application.

### STORAGE

Store at room temperature with container tightly sealed.

### CLEAN UP

Wash tools with water.

### CAUTION

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only.

If sanding is necessary, use a dust-particulate respirator approved by NIOSH-MSHA.



| VELLA PART # | DESCRIPTION                    | SIZE     | WEIGHT    | UPC CODE        |
|--------------|--------------------------------|----------|-----------|-----------------|
| 30032        | VELLA PREMIUM VENETIAN PLASTER | 3.5 GAL. | 41 LBS.   | 0 00516 30032 8 |
| 30016        | VELLA PREMIUM VENETIAN PLASTER | 1 GAL.   | 12 LBS.   | 0 00516 30016 8 |
| 30004        | VELLA PREMIUM VENETIAN PLASTER | 1 QT.    | 2.75 LBS. | 0 00516 30004 5 |

### SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM

**SUBMITTAL APPROVALS**

JOB NAME:

CONTRACTOR:

DATE:

SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • [WWW.VELLAPLASTER.COM](http://WWW.VELLAPLASTER.COM)

NEW PRODUCT  
NOW AVAILABLE



# VELLA

VENETIAN PLASTER SYSTEMS



## VELLA PREMIUM PLASTER WAX

### DIRECTIONS

Apply Vella Premium Plaster Wax using a sponge applicator or cloth. Cover entire surface area using a circular motion, massaging wax into a dry plastered surface. Polish surface using a soft cloth or a mechanical buffer to achieve desired sheen. A second coat of wax may be applied by sponge applicator, spatula or trowel to increase hardness and shine of plaster. Polish surface to desired sheen.

*Vella Premium Plaster Wax is designed to create a protective seal and add a beautiful luster to venetian plasters. This formulated low odor wax may be used on large areas, leaving a pleasant scent.*

### CAUTION

FLAMMABLE: Keep out of reach of children. If swallowed, do not induce vomiting. Seek medical attention.



| VELLA PART# | DESCRIPTION                         | SIZE   | WEIGHT | UPC CODE        |
|-------------|-------------------------------------|--------|--------|-----------------|
| 30001       | VELLA PREMIUM PLASTER WAX, CLEAR    | 1 GAL. | 6 LBS. | 0 00516 30090 8 |
| 30008       | VELLA PREMIUM PLASTER WAX, CLEAR    | 1 QT.  | 22 OZ. | 0 00516 30008 3 |
| 30001-W     | VELLA PREMIUM PLASTER WAX, WALNUT   | 1 GAL. | 6 LBS. | 0 00516 30090 8 |
| 30008-W     | VELLA PREMIUM PLASTER WAX, WALNUT   | 1 QT.  | 22 OZ. | 0 00516 30008 3 |
| 30008-M     | VELLA PREMIUM PLASTER WAX, MAHOGANY | 1 QT.  | 22 OZ. | 0 00516 30008 3 |

### SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM

**SUBMITTAL APPROVALS**

JOB NAME:

CONTRACTOR:

DATE:

SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • [WWW.VELLAPLASTER.COM](http://WWW.VELLAPLASTER.COM)

NEW PRODUCT  
NOW AVAILABLE



# VELLA

VENETIAN PLASTER SYSTEMS

## VELLA METALLICS



*Vella metallic pigments are designed to create specialized finishes over Vella and Liscio products, adding beauty and luster to the finished product. The combination of effects are limitless when applied over different colors and textures of Venetian Plasters. Create your own Signature Series of custom finishes.*

### APPLICATION

#### MIXING VELLA METALLIC PIGMENTS

**STEP 1:** Standard mixing of metallic powder is added to Vella Clear or Colored Waxes at a ration of 2oz. Metallic powder to 1qt. of wax, creating a metallic wax substance. Using a clean container, add the proper ratio of metallic powder to the wax and thoroughly mix with a small putty knife, stir stick or a small mechanical beater (kitchen utensils make great tools).

*Tip: Adding small amounts of the ratio to the container while mixing will be easier to mix than dumping the full amount in all at once.*

After product is completely mixed it is ready to apply or be stored, until ready for use. To properly store or save unused product, keep it in a sealed container out of direct sunlight in a cool place.

*(Continued on back of sheet)*



| VELLA PART# | DESCRIPTION                            | SIZE            | WEIGHT | UPC CODE        |
|-------------|--|-----------------|--------|-----------------|
| 30021       | VELLA METALLICS, M-7 MAGNA PEARL       | 2 OZ. CONTAINER | 17 G.  | 0 00516 30021 2 |
| 30022       | VELLA METALLICS, M-5 LUMINA GOLD       | 2 OZ. CONTAINER | 20 G.  | 0 00516 30022 9 |
| 30023       | VELLA METALLICS, M-6 TURQUOISE         | 2 OZ. CONTAINER | 30 G.  | 0 00516 30023 6 |
| 30024       | VELLA METALLICS, M-2 BLACK OLIVE       | 2 OZ. CONTAINER | 14 G.  | 0 00516 30024 3 |
| 30025       | VELLA METALLICS, M-4 NU-ANTIQUE GOLD   | 2 OZ. CONTAINER | 17 G.  | 0 00516 30025 0 |
| 30026       | VELLA METALLICS, M-3 NU-ANTIQUE BRONZE | 2 OZ. CONTAINER | 17 G.  | 0 00516 30026 7 |
| 30027       | VELLA METALLICS, M-1 MICRO BRASS       | 2 OZ. CONTAINER | 20 G.  | 0 00516 30027 4 |
| 30028       | VELLA METALLICS, M-8 MERLIN SILVER     | 2 OZ. CONTAINER | 14 G.  | 0 00516 30028 1 |
| 30029       | VELLA METALLICS, M-9 BRIGHT GOLD       | 2 OZ. CONTAINER | 20 G.  | 0 00516 30029 8 |

### SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM

# VELLA METALLICS

*(Continued from the front)*

- ❖ **OPTIONS:** Ratio of metallic powders can be increased or decreased from the standard ratio to create the desired effect you want to achieve. You may also add multiple metallic powders in the mixing process when attempting to create a certain hue, shade or tone of a metallic color. It is recommended to log all ratios used, rather than guessing on how you made that color.

## TECHNIQUES FOR VELLA METALLIC FINISHES

**STEP 2:** Standard application technique for metallic finishes are achieved using a small detailed spatula from 3" to 6" for controlled purposes. Metallic wax is applied over finished Venetian Plaster surfaces that have been wax sealed and are dry (usually 2-4 hours, depending on conditions). Apply small amount of metallic wax by spatula using even pressure in a cross-hatched pattern with complete coverage. The product should be applied tight

(no excess or residue build-up) in a delicate wipe-on, wipe-off method. Allow metallic wax to dry by touch and polish using a smooth cloth or mechanical buffer.

*Tip: Maintaining a small amount of metallic wax to the center of application spatula will help control the amount being applied and greatly reduce possible excess material build-up. Proper application will provide an even surface and uniform drying time. Any touch-ups or missed areas should be done after original application has dried to touch and blended into the original pattern.*

- ❖ **OPTIONS:** Multiple metallic wax colors may be applied during the application process or over one another, creating a custom or patina type effect. It is recommended to log the colors used, allowing you to duplicate the finish when needed. Metallic wax may also be applied by sponge or rags to create unusual effects.

*This instruction sheet was created to offer ideas and recommendations for the use of Vella Metallic Pigments by professional applicators. Results may vary according to application techniques.*

## SUBMITTAL APPROVALS

JOB NAME:

CONTRACTOR:

DATE:

## SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM