VELLA
VENETIAN PLASTER SYSTEMS

Submittal Sheet

MARBLE SERIES

Fine Marmorino



Fine Marmorino

Authentic Marmorino Plaster made of fine crushed marble for interior walls and ceilings. Add Coarse Marble Aggregate for rougher stone texture.

Marble Series: Classic Vella interior finishes. The natural beauty of marble, from soft velvet to high polish.

MADE IN THE USA

What is it?

Vella Marble Series Fine Marmorino is an interior acrylic plaster made with finely crushed marble and stone. It creates the soft, stone-like texture of traditional Italian Marmorino, from sleek and contemporary to rustic and old-world, with gentle movement and tonal variation across the wall.

It goes directly over level 3 drywall and existing painted surfaces. Leave it matte, or sand and wax for a soft sheen. Want a grainier, more textured stone look? Mix in Vella Coarse Marble Aggregate to turn Fine Marmorino into Coarse Marmorino.

Benefits

- **Authentic Marmorino Finish.** Finely crushed marble gives a real stone texture with soft tonal variation.
- **Fine or coarse.** Use as is for a fine finish, or add Coarse Marble Aggregate for a coarse, textured stone look.
- **Goes right over drywall.** Applies directly over level 3 drywall and existing painted surfaces.
- **Matte or soft sheen.** Leave it matte, or sand with 325 grit or finer and add Vella Clear Wax for a gentle sheen.
- **Sandable and patchable.** Easy repairs and touch-ups.
- **Zero VOC.** No harsh odor during application.
- **A lower price point.** The classic Vella products for interior projects on a budget. Not for showers, wet areas or exterior surfaces; for those, choose a Diamond Series product.
- **Made in the USA** by Vella Venetian Plaster Systems, serving Southern California since 2005.

HAZARD: May cause cancer (inhalation). May cause damage to organs (eye, lung, kidney, liver, thyroid gland and immune system) through prolonged and repeated exposure (oral and inhalation). **CAUTION:** Avoid contact with eyes or prolonged contact with skin. May cause an allergic skin reaction. Wash thoroughly after handling (see SDS Section 8). In case of eye contact, flush immediately with running water for several minutes; if irritation persists, consult a physician. Provide adequate ventilation in enclosed areas; use of an approved respirator is recommended. **WARNING:** This product can expose you to Crystalline Silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. If dry sanding, wear a NIOSH-approved dust mask and eye protection. Keep out of reach of children. See SDS for complete safety information.
WARRANTY: Since methods and conditions of application and use are beyond our control, our warranties shall not be effective UNLESS the product is applied according to our current printed directions and specifications. The manufacturer shall replace such quantity of products proven to be defective within 1 year following date of manufacture.

Showroom and Training Center: 2180 N. Glassell, Orange CA 92865
Phone: (714) 279-0240 | Fax: (714) 279-1043
www.vellaplaster.com

Fine Marmorino Product Data Sheet

1. Packaging

42 lbs. (19.05 kg) net weight in 3.5-gallon plastic pail / 48 pails per pallet.
12 lbs. (5.44 kg) net weight in 1-gallon plastic pail / 96 pails per pallet.
3 lbs. (1.36 kg) net weight in 1-quart plastic pail.

2. Storage

Protect from direct sunlight and keep from freezing. Do not stack more than 3 pails high. Shelf life of 12 months. Tightly seal lid when storing.

3. Coverage

Approximately 150 - 200 ft² per 3.5-gallon pail (42 lbs.) and 30 - 60 ft² per 1-gallon pail (12 lbs.), depending on surface conditions and thickness of application.

4. Mixing

Thoroughly mix with a drill motor and paddle mixer to a smooth, even consistency and color. **COARSE MARMORINO:** add Vella Coarse Marble Aggregate: one 5 lb. bag per 3.5-gallon pail, 1¾ cups per gallon, or ½ cup per quart, and mix thoroughly.

5. Drying Time

Dry to the touch in approximately 1 - 2 hours at 68°F (20°C) with good ventilation.

6. Clean-Up

Wash tools and equipment with water.

7. Job and Surface Conditions

Interior use only. Substrate must be dry, clean, sound, and free from contaminants such as dust, oil, mildew, debris, and efflorescence. Maintain a minimum air temperature of 40°F (4.4°C) during application, and at least 48 hours afterwards. May be applied over new or previously painted surfaces and level 3 drywall; glossy surfaces must be roughed to ensure proper bond. Pre-priming over wallpaper recommended. **MASONRY, CONCRETE AND PLASTER:** Surfaces should cure for a minimum of 7 days prior to application. **POURED CONCRETE:** Surfaces should cure for a minimum of 28 days prior to finishing. Not for showers, wet areas or exterior surfaces.

8. Thinning

Do not thin product.

9. Application

BASE COAT: Apply a tight putty coat over the entire surface with a standard stainless steel, plastic vinyl, Venetian plaster, or drywall trowel. For more uniform color, smooth out lap lines as product sets. To avoid chatter marks, use more material, keep trowel flat and do not pull as tight. Scrape down lap lines when dry for more character, sand them down for a more subtle finish. **TOP COAT:** Repeat steps from base coat and trowel smooth as product sets. If texture is desired, leave pockets of base coat in random areas, then trowel smooth. **FINISH:** Leave matte, or sand with 325 grit or higher for desired finish. NOTE: Higher grit and wax increase "burnish".

10. Pro Tips

LIGHT COLORS: Use a plastic or "white out" trowel to avoid gray burnish marks. **MORE TEXTURE:** Add Coarse Marble Aggregate for a grainier, natural stone look. **ADD SHEEN:** Finish with Vella Clear Wax, or Vella Metallics for shimmer. **MAKE A SAMPLE FIRST:** Test color and technique on a sample board before starting a wall.

Submittal Approval

Job Name:

Contractor: **Date:**

Showroom and Training Center: 2180 N. Glassell, Orange CA 92865
Phone: (714) 279-0240 | **Fax:** (714) 279-1043
www.vellaplaster.com