



# VELLA

VENETIAN PLASTER SYSTEMS



## VELLA PREMIUM VENETIAN PLASTER

### APPLICATION

**STEP 1:** Prepare by covering areas not to be plastered. Apply base coat to surface as evenly as possible. Cover textures or blemishes using a trowel, spatula or paint roller. Vella Premium Venetian Plaster may be used over new or previously painted surfaces. Surfaces must be dry, clean, firm and free of dust, dirt, oil, wax, loose paint, wallpaper and plaster.

- ❖ When using a paint roller, use a trowel or spatula to smooth over any stipple left by the roller before the plaster dries. Plaster should dry overnight. Depending on weather conditions, fans may be used to speed up the drying process.

**STEP 2:** After plaster base coat dries, in a random pattern apply a thin coat of plaster over the base coat using a trowel or spatula.

*Tip: Any ridges in the base coat may be scraped off with a spatula prior to applying the second coat. Tools should be clean and smooth before applying plaster. Use fine sandpaper to keep tools smooth and free of nicks.*

- ❖ Additional troweling of plaster after the second coat has set up will produce a higher sheen to the finished surface.

**STEP 3:** After second coat dries (usually 4 hours, depending on weather conditions), apply a thin coat of Vella Premium Plaster Wax or sealer by sponge, rag or trowel to the entire surface. Final polishing of the surface should be done approximately 15 minutes after waxing using a dry rag or mechanical buffer.

### MIXING

Add desired color (store will mix). If adding your own color, mix with drill and paddle.

### COVERAGE

Vella Premium Venetian Plaster covers approximately 100 square feet per gallon depending on textures and application.

### STORAGE

Store at room temperature with container tightly sealed.

### CLEAN UP

Wash tools with water.

### CAUTION

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only.

If sanding is necessary, use a dust-particulate respirator approved by NOSHA-MSHA.



| VELLA PART# | DESCRIPTION                    | SIZE     | WEIGHT    | UPC CODE        |
|-------------|--------------------------------|----------|-----------|-----------------|
| 30032       | VELLA PREMIUM VENETIAN PLASTER | 3.5 GAL. | 41 LBS.   | 0 00516 30032 8 |
| 30016       | VELLA PREMIUM VENETIAN PLASTER | 1 GAL.   | 12 LBS.   | 0 00516 30016 8 |
| 30004       | VELLA PREMIUM VENETIAN PLASTER | 1 QT.    | 2.75 LBS. | 0 00516 30004 5 |

### SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

• OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM